

MODELS - DIGITAL MOISTURE METER

TECHNICAL SPECIFICATIONS & SALIENT FEATURES

- * Confirms to IS-8824-Part-I-1978
- * Calibrated & tested as per IS
- * Measuring Range : 0 % to 40.0%
- * Sensitivity: + 0.1%
- * Accuracy: + 0.2%
- * Meter Weight: Less than one Kg
- * Power: Four pencil cells
- * No mechanical moving parts hence no wear & tear & long maintenance free operation.
- * Automatic inbuilt temperature compensation provided.
- * “LOBAT” / “BAT” on display for weak pencil cells.
- * ABS Molded body for long rugged used in field.
- * Non-destructive sample testing.
- * Display : 3 1/2 LCD
- * Power requirement: Four pencil cells
- * Measurement time: one sample per minute



DMM - Regular Model



DMM - N SERIES



DMM - V SERIES

ADDITIONAL FEATURES

- * Auto calibration check facility
- * Empty Reading in all channels is “00.0”



DMC312 - REGULAR MODEL



DMC312 - N SERIES



DMC312 - V SERIES

ADDITIONAL FEATURES

- * Auto calibration check facility
- * Empty Reading in all channels is “00.0”
- * Display : 16 X 2 Alpha Numeric with Item Name & Quantity on display



DMC162 - REGULAR MODEL



DMC162 - N SERIES



DMC162 - V SERIES